


lumeplus



2016 Product Catalog



Why
LED?

It's simple... LED Lighting
saves you money and is
environmentally friendly



Who
are
We?

lumeplus is a reliable
supplier of Indoor & Outdoor
Lighting, specialising in
Architectural and LED Solu

lumeplus

Contents

Indoor Lighting	LED Mini Downlight
	
Indoor Lighting	
	
Outdoor Lighting	LED Underground light
	
Outdoor Lighting	LED Garden light
	



LED Recessed Light

Applications:

Room decorative lighting, KTV
Cabinet showcase, stairway, hallway
Club, Hotel and so on.



Mini LED Downlight

Product number: TMSS-Y1W

Power: 1W

Luminous flux: 95Lm

Color: >80Ra

Beam angle: 120°

Light type: LED

Input voltage: DC3V/300mA

Color temperature : 3000K(WW)、4000K(W)、6000K(CW)


Other light color : Red , Blue , Green

Light body material: aluminum


Operating temperature:-25°~+45°

Protection: IP65


Life: 35000h




High temperature silicone copper core wire



Constant current power supply transformer



Constant current power supply transformer



Mini LED Downlight

Product number: TMSS-Y1W

Power: 1W

Luminous flux: 95Lm

Color: >80Ra

Beam angle: 120°

Light type: LED

Input voltage: DC12V

Color temperature : 3000K(WW)、4000K(W)、6000K(CW)


Other light color : Red , Blue , Green

Light body material: aluminum

Operating temperature:-25°~+45°

Protection: IP65


Life: 35000h





Unit: mm



DC12V/1W
Parallel connection





Mini LED Downlight

Product number: TMDT-Y1W

Power: 1W

Luminous flux: 95Lm

Color: >80Ra

Beam angle: 60°

Light type: LED

Input voltage: DC3V

Color temperature : 3000K(WW)、4000K(W)、6000K(CW)


Other light color : Red , Blue , Green

Light body material: aluminum

Operating temperature:-25°~+45°


Protection: IP65

Life: 35000h




Unit: mm


 **IP65**



High temperature silicone copper core wire




Constant current power supply transformer



Constant current power supply transformer

lumeplus



3V/630mA-3W

DC12-24V-3W

LED cabinet lights / downlight

Product number: TMCG-Y4W

Power: 3W

Luminous flux: 280Lm

Color: >80Ra

Beam angle: 25° 60° Conventional production: 25°

Light type: LED

Input voltage: DC3V or DC12-24V


Color temperature : 3000K(WW)、4000K(W)、6000K(CW)

Light body material: aluminum

Operating temperature:-25°~+45°

Protection: IP42


Life: 35000h




(DC3V/630mA)




Unit: mm



(DC12-24V)





Surface mounted LED Cabinet Light

Product number: MZCG-3W-A

Power: 3W

Luminous flux: 295Lm

Color: >80Ra

Beam angle: 90°

Light type: LED

Input voltage: AC95-120V AC195-240V

Color temperature : 3000K(WW)、4000K(W)、6000K(CW)

Light body material: aluminum

Operating temperature:-25°~+45°

Protection: IP65


Life: 35000h



Unit: mm



Dimmable



Outdoor Lighting



LED Buried lights

Product number: TMDM-Y1W-A

Power: 1W-3W

Luminous flux: 95Lm-250Lm

Color: >80Ra

Beam angle: 15° 45° 60° Conventional production: 45°

Light type: LED

Input voltage: DC12-24V

Color temperature : 3000K(WW)、4000K(W)、6000K(CW)


Other light color : Red , Blue , Green

Light body material: Cover (stainless steel), lamp body (aluminum)


Operating temperature:-25°~+45°

Protection: IP67

Life: 35000h




(1W)



(3W)

Unit: mm



lumeplus



LED Inground Light




Product Parameters :

Product Code : TMDM-3W-B
 Power : 3W
 Luminous Flux : 280lm
 CIR : >80Ra
 Voltage : DC12-24V
 LED Type : Epistar COB LED
 IP Rate : IP67
 Color : Warm White(3000K), Nature White(4000K), Cool White(6000K)
 Main Materials : Cover(Stainless Steel), Lamp body(Aluminum)

Lamp Size :


Unit : mm




Embedded part size :



ABS material



lumeplus



Product packaging





Side Emitting LED lights and buried

Product number: TMDM-Q3W

Power: 3W

Luminous flux: 280Lm

Color: >80Ra

Beam angle: Single optical port, dual optical port, Sanko port

Light type: LED

Input voltage: DC12-24V



Color temperature : 3000K(WW)、4000K(W)、6000K(CW)

Light body material: Aluminum 6063

Operating temperature:-25°~+45°

Protection: IP67

Life: 35000h

Q1



Q2




Q3



Lamp Size :


Unit : mm




Embedded part size :



ABS material



lumeplus




Aerial view




side view



bottom





LED Footlights

Product number: TMJT-Y1W-A

Power: 1W

Luminous flux: 95Lm

Color: >80Ra

Optional light outlet category: A1 A2 A3

Light type: LED

Input voltage: DC12-24V

Color temperature : 3000K(WW)、4000K(W)、6000K(CW)


Other light color : Red , Blue , Green

Light body material: aluminum

Operating temperature:-25°~+45°

Protection: IP67

Life: 35000h




Unit: mm


A1

A2

A3



Connection:



DC12-24V power supply, parallel installation

lumeplus



LED underwater lights

Product number: TMXD-3W-A

Power: 3W

Luminous flux: 280Lm

Color: >80Ra

Beam angle: 30° 60°

Light type: LED

Input voltage: DC12-24V

Color temperature : 3000K(WW)、4000K(W)、6000K(CW)


Other light color options: green, red , blue

Light body material: Cover (stainless steel), lamp body (aluminum)

Operating temperature:-25°~+45°


Protection: IP67

Life: 35000h




Unit: mm

 **IP68**



Connection:




DC12-24V power supply, parallel installation

lumeplus



LED garden lights



Product number: DETY-3W-A

Power: 3W

Luminous flux: 280Lm

Beam angle: 30°

Light type: LED

Color: 80Ra

Input voltage: DC12-24V


Color temperature : 3000K(WW)、4000K(W)、6000K(CW)

Light body material: Aluminum 6063

Operating temperature:-25°~+45°


Protection: IP67

Life: 35000h





lumepius



LED Lawn

Product number: DECP-5W-A

Power: 5W

Luminous flux: 480Lm

Color: >80Ra

Beam angle: 30° or 60°

Light type: LED

Input voltage: DC12-24V



Color temperature : 3000K(WW)、4000K(W)、6000K(CW)

Light body material: Aluminum 6063

Operating temperature:-25°~+45°

Protection: IP67

Life: 35000h



lumeplus





LED handrail / railing Light

Product number: DEFS-1W-A

Power: 1W

Luminous flux: 95Lm

Color: >80Ra

Beam angle: 120°

Light type: Epistar LED

Input voltage: DC12V

Color temperature : 3000K(WW)、4000K(W)、6000K(CW)


Other light color : Red , Blue , Green

Light body material: Cover (stainless steel), lamp body (aluminum)

Operating temperature:-25°~+45°



Protection: IP67

Life: 35000h



Unit: mm







Reference installation diagram:




1. The use special steel drill 27mm drilling





2. The lamp body within the wire into the tube, butt



3. The lamp body inserted into the hole, and then fixed position



4. access to power, turn on





Recessed LED Footlights

Product number: DEDB-1W-A

Power: 1W

Luminous flux: 95Lm

Color: >80Ra

Beam angle: 120°

Light type: 5050SMD LED

Input voltage: DC12

Color temperature : 3000K(WW)、4000K(W)、6000K(CW)


Other light color : Red , Blue , Green

Light body material: Cover (stainless steel), lamp body (aluminum)

Operating temperature:-25°~+45°

Protection: IP67

Life: 35000h






Unit: mm



lumeplus


Lamp body Description:





DE-YM01-41

DE-YM01-35



The following products are suitable for use



TMDM-3W-B



TMDM-C3W-A



TMDM-Y3W - A



TMTJ-1W



TMXD-3W-A





DE-F23 4mm 4P/4C 10A 1000V 10m



Product Code: DE-F23
Diameter: 4mm
Cortical Material: PVC
Conductor: Copper



Parallel shunt line

Connection method:

