



### Cylindrical Opalised Polycarbonate LED Downlight

Fixed surface downlight, providing direct and diffuse light, The Surface cylindrical downlight by Lumeplus, comprises of an aluminum housing, with a polycarbonate diffuser with flush black glossy rim offers a choice of colour temperature and CRI . Remote Dali driver design with a stylish appearance, easy to install, paying more attention to leisure and comfort.

It gives space lively feeling Different finishes rims creates diversified light atmosphere .The lamp reflector light output is > 86% using AL6063 Aluminum radiator in sand blast oxidation treatment provides excellent heat dissipation and corrosion resistance.

Lighting Area 2-4square meters

LED power: 12W/20W/30W

Luminous Flux: 100-110lms/W

Optics 15°/24°/36° beam angle

LED source CREE COB

Color temperature 3000K.4000K.6000K

Input voltage AC85-265V

Lifespan ≥40000h

Working temperature -30°~50°C

Protection Grade IP20 Class II CE

Dimension Dia76mm/96mm/116mm\*H150mm

Remote Dali Driver body made of fire resistant ABS Material.

Composed of Constant current power supply and intelligent integrated circuits PF>0.9

### Make:Lume-PlusSurfaceMountLP-LF06-12W/20W/30W

NARROW BEAM ANGLE    MEDIUM BEAM ANGLE    WIDE BEAM ANGLE    EXTRA WIDE BEAM ANGLE

