

Round
Øk

Powered BY
TRIDONIC **OSRAM** **NICHIA** **EUCHIPS**



Technical data:

Wide Optics LED Downlight

Excellent LED downlight directional or fixed accent or ambient application made of Die cast aluminum body robust design using radiation thermal heat sink the reflector has a secondary optical design and the LED chip is protected with a Stent for perfect light distribution . The wire harness is fire-resistance ,mounting spring clips made of high tension springs for easy installation .

Lighting Area 3-4 square meters

Optics 60° beam angle

input voltage AC85-265V

LED power 30W

Luminous Flux: 2600Lm

LED source Citizen -CREE -Bridgelux COB LED 85lm per

watt Color temperature 3000K 4000K 6000K

Lifespan ≥50000h

Working temperature -30°~50°C

CE, IP43 Protection Class II

Dimension Diameter 175 Height 115mm



Hole Cut Out Diameter 165 -170mm

Driver body made of fire resistance ABS Material

composed of Constant current power supply and

intelligent integrated circuits PF>0.9

Make: Lumeplus LP-R1005-30W



Beam angle: 38°

H (m)	E0 (lx)	Dh (M)
1.0	3966.04	0.61
2.0	991.51	1.21
3.0	440.67	1.82
4.0	247.88	2.43
5.0	158.64	3.04
6.0	110.17	3.64

